

PRELIMINARY AMENDMENT

Int'l Appln. PCT/HU2002/000147

-2-

July 14, 2005

Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

1. A collapsible toilet made of sheet material, the toilet comprising side walls connected to each other at their lateral edges and defining an inner space of the toilet, a seat surface arranged at the upper edges of the side walls, and fold-lines for collapsing the toilet, ~~e-h-a-r-a-c-t-e-r-i-s-e-d~~ by comprising

two opposite holding side walls (~~21e, 21f~~) having top edges (~~51a, 51b~~) to which two edges of an annular seat surface are joined respectively along respective fold-lines, and

supporting side walls (~~21a, 21b, 21d, 21e~~) connecting the holding side walls (~~21e, 21f~~) and having upper edges (~~42a, 42b, 42d, 42e~~) forming a supporting periphery that supports the seat surface,

wherein in the seat surface a fold-line is arranged at an equal distance from the top edges (~~51a, 51b~~) of the holding side walls (~~21e, 21f~~), said fold-line enabling folding the seat surface into the inner space (~~4~~) when the holding side walls (~~21e, 21f~~) are moved towards each other.

2. The toilet according to claim 1, ~~characterised in that~~ wherein the seat surface is fixed to the supporting periphery at least at one location.

3. The toilet according to claim 2, ~~characterised in that~~ wherein the seat surface consists of seat surface segments (~~12a, 12b~~), the said seat surface segments (~~12a, 12b~~) comprising a basic portion (~~22a, 22b~~) joining the top edge (~~51a, 51b~~) of the holding side wall (~~21e, 21f~~) and two lateral parts (~~23a, 24a; 23b, 24b~~) extending towards the other seat surface segment (~~12a, 12b~~), wherein opposite lateral parts (~~23a, 24a; 23b, 24b~~) of the seat surface segments (~~12a, 12b~~) are joined at their ends to each other along the fold-line, and wherein a fixing to the supporting periphery is located at the joining portions of the lateral parts (~~23a, 24a; 23b, 24b~~).

PRELIMINARY AMENDMENT

Int'l Appln. PCT/HU2002/000147

-3-

July 14, 2005

4. The toilet according to claim 3, ~~characterised in that it~~ wherein the seat surface is formed of a single piece of sheet material by cutting and gluing, wherein each seat surface segment (~~12a, 12b~~) is continuous with the respective holding side wall (~~21e, 21f~~) separated from it by a fold-line, and the ends of the lateral parts (~~23a, 24a; 23b, 24b~~) are provided with flaps (~~25a, 26a; 25b, 26b~~) bent perpendicular to the seat surface and glued to each other in pairs extending towards the supporting periphery, wherein the flaps (~~25a, 26a; 25b, 26b~~) have slots (~~33a, 34a; 33b, 34b~~) and are pressed with the slots (~~33a, 34a; 33b, 34b~~) on the supporting periphery or into further slots (~~31, 32~~) in the supporting periphery.

5. The toilet according to claim 4, ~~characterised in that~~ wherein there are two further fold-lines (~~52a, 52b; 52c, 52d~~) in each seat surface segment (~~12a, 12b~~) extending across a respective endpoint of the top edge (~~51a, 51b~~) of the holding side wall (~~21e, 21f~~) and normal to the edge (~~51a, 51b~~), the two further fold-lines (~~52a, 52b; 52c, 52d~~) separating the basic portion (~~22a, 22b~~) from the lateral parts (~~23a, 24a; 23b, 24b~~), wherein the lateral parts (~~23a, 24a; 23b, 24b~~) are folded on the top surface of the basic portion (~~22a, 22b~~) along these further fold-lines (~~52a, 52b; 52c, 52d~~) when folding the toilet (~~1~~), and the seat surface segments (~~12a, 12b~~) are folded into the inner space (~~4~~) with the upright flaps (~~25a, 26a; 25b, 26b~~) by pushing the holding side walls (~~21e, 21f~~) together.

6. The toilet according to claim 5, ~~characterised by~~ having a hexagonal inner space (~~4~~), the two holding side walls (~~21e, 21f~~) are connected to each other by pairs of supporting side walls (~~21a, 21b; 21d, 21e~~) on the two sides, and the slots (~~31, 32~~) in the supporting periphery are formed in each pair along the joint lateral edge (~~54a, 54d~~) of the supporting side walls (~~21a, 21b, 21d, 21e~~).

7. The toilet according to claim 6, ~~characterised by~~ having a folded position, in which the pairs of the supporting side walls (~~21a, 21b; 21d, 21e~~) are folded onto the outside of the respective pushed-together holding side walls (~~21e, 21f~~).

PRELIMINARY AMENDMENT

Int'l Appln. PCT/HU2002/000147

-4-

July 14, 2005

8. The toilet according to claim 1, ~~characterised in that~~ wherein a receptacle bag ~~(2)~~ open at the top is fixed by a releasable joint to the seat surface segments ~~(12a, 12b)~~ or to the side walls.

9. The toilet according to claim 1, ~~characterised in that it~~ is made of corrugated paperboard or plastic.